PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7:	A1	(11) International Publication Numbe	r: WO 00/55261
C09D 1/02		(43) International Publication Date:	21 September 2000 (21.09.00)

EP

(21) International Application Number: PCT/EP00/02547
 (22) International Filing Date: 17 March 2000 (17.03.00)

(71) Applicant (for all designated States except US): INTERNA-

18 March 1999 (18.03.99)

(71) Applicant (for all designated States except US): INTERNATIONAL COATINGS LTD. [GB/GB]; Oriel House, 16 Connaught Place, London W2 2ZB (GB).

(72) Inventors; and
(75) Inventors/Applicants (for US only): DAVIES, Gerald, Howard [GB/GB]; 11 Castleton Grove, Jesmond, Newcastle-upon-Tyne NE2 2HD (GB). JACKSON, Paul, Anthony [GB/GB]; 38 Hazelmoor, Hebburn Village, Hebburn, Tyne & Wear (GB). MCCORMACK, Peter, Joseph [GB/GB]; 5 Meldon Terrace, Heaton, Newcastle-upon-Tyne NE6 5XP (GB). BANIM, Fiachra [IE/IE]; 1 Seapoint, Balbriggan, County Dublin (IE).

(74) Agent: SCHALKWIJK, Pieter, Cornelis; Akzo Nobel N.V., Intellectual Property Dept. (Dept. AIP), P.O. Box 9300, NL-6800 SB Arnhem (NL). (81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published

With international search report.

(54) Title: PRIMER COATING OF STEEL

(57) Abstract

(30) Priority Data:

99302127.8

The present invention relates to a process for primer coating of steel which is intended to be fabricated and overcoated, in which process the steel is primer coated with a primer coating comprising a silica or silicate binder, wherein the binder comprises an aqueous silica sol or alkali metal silicate having a SiO₂/M₂O mole ratio, where M represents total alkali metal and ammonium ions, of at least 6:1, and that after the primer coating has dried to the extend that it is touch dry it is treated with a solution which increases the film strength of the primer coating.

ather with with mild to